



EOK: ELECTRIC OSCILLATING TOOL

TOOL	BLADE	UNDERLAY
Bullmer EOK is especially suitable for 3.0 mm and 5.0 mm KATZ DISPLAY BOARDS.	Oscillating knife for cutting fine structures.	Grey bullmer standard cutting felt in 4 mm thickness for optimum cutting quality with bullmer digital cutting machines.
· Compatible Bullmer premiumcut elc	· RS 10	· Thickness: 4.0 mm

	Blade type	Blade length	Speed m/min				l lo do do d	Accelera-
			20	30	50	60	Underlay	tion
1.2 mm	RS 10	15 mm				X	Felt: 4 mm	1.8
1.6 mm	RS 10	15 mm				X	Felt: 4 mm	1.7
2.0 mm	RS 10	15 mm			X		Felt: 4 mm	1.5
3.0 mm	RS 10	15 mm		X			Felt: 4 mm	1.5
5.0 mm	RS 10	15 mm	X				Felt: 4 mm	1.5





DK: STATIC KNIFE TOOL

TOOL BLADE **UNDERLAY** Bullmer DK is especially suitable for Static knife, for rather thin Grey bullmer standard cutting felt in 4 mm KATZ DISPLAY BOARDS. KATZ DISPLAY BOARDS in the thicknesses thickness for optimum cutting quality with bullmer 1.2 mm; 1.6 mm; 2.0 mm and 3.0 mm. It allows fast speed. digital cutting machines. It allows very fast cutting speeds with the static knife. · Compatible Bullmer premiumcut elc · B 16 · Thickness: 4.0 mm · Knife length in total 25 mm

KATZ DISPLAY BOARDS thickness	Blade type	Blade length	Speed m/min				· Underlay	Accelera-
			50	80	90	100	Unaenay	tion
1.2 mm	B 16	7.4 mm*				X	Felt: 4 mm	1.6
1.6 mm	B 16	7.4 mm*			X		Felt: 4 mm	1.6
2.0 mm	B 16	7.4 mm*		X			Felt: 4 mm	1.6
3.0 mm	B 16	7.4 mm*	Χ				Felt: 4 mm	1.6
5.0 mm	B 16	not recommended						





RRA: CREASING TOOL

TOOL

The RRA is very good for processing KATZ DISPLAY BOARD 1.2 mm, 1.6 mm and even 2.0 mm. It produces high-quality creases for folding KATZ DISPLAY BOARD.

- · Compatible Bullmer premiumcut elc
- · Makes KATZ DISPLAY BOARDS foldable without cracking



BLADE

Recommended use: For solid board and paper based board.


· Creasing wheel 2415



UNDERLAY

Grey bullmer standard cutting felt in 4 mm thickness for optimum cutting quality with bullmer digital cutting machines.

·· Thickness: 4.0 mm



KATZ DISPLAY BOARDS	Creasing	Pressure	Speed m/min	Underlay	Accelera-		
thickness	rness Tool riessule 60	onaenay	tion				
1.2 mm	2415	n.a.	X	Felt: 4 mm	1.6		
1.6 mm	2415	n.a.	X	Felt: 4 mm	1.6		
2.0 mm	2415	n.a.	X	Felt: 4 mm	1.6		
3.0 mm	2415		not recommended				
5.0 mm	2415		not recommended				





DKV: V-CUT TOOL

TOOL

This tool is used for pro-ducing KATZ DIS-PLAY BOARD with V-Cut.

V-Cut allows folding of different board thicknesses.

- · Compatible Bullmer premiumcut elc
- · Cuts at 6 different angles (0°, 15°, 22.5°, 30°, 45°, 60°)



BLADE

Stable V-Cut knife, suitable to cut all 6 angles from 0° up to 60°


- · B 71
- · Knife length in total 50 mm



UNDERLAY

Grey bullmer standard cutting felt in 4 mm thickness for optimum cutting quality with bullmer digital cutting machines.

· Thickness: 4.0 mm



	Blade	Blade length		· Underlay	Accelera-		
	type		40	50	60	Underlay	tion
1.2 mm	B 71	11.8 mm*			X	Felt: 4 mm	1.5
1.6 mm	B 71	11.8 mm*			X	Felt: 4 mm	1.5
2.0 mm	B 71	11.8 mm*		X		Felt: 4 mm	1.5
3.0 mm	B 71	11.8 mm*	X			Felt: 4 mm	1.5
5.0 mm	B 71	11.8 mm*	X			Felt: 4 mm	1.5

^{*} Value corresponds to cutting depth





Contact



Philipp Reuter Junior Sales Manager KATZ Display Board

Phone +49 7224 647-206 Fax +49 7224 647 10-206 philipp.reuter@thekatzgroup.com